

529,126

Rec'd PCT/PTO 24 MAR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number
WO 2004/029476 A1

(51) International Patent Classification⁷: **F16F 15/28**

(21) International Application Number:
PCT/GB2003/004055

(22) International Filing Date:
23 September 2003 (23.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0222480.6 27 September 2002 (27.09.2002) GB

(71) Applicant (for all designated States except US): **RICARDO UK LIMITED** [GB/GB]; Bridge Works, Shoreham-by-Sea, West Sussex BN43 5FG (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **STOTT, Michael,**

Robert [GB/GB]; 25 Fairview Road, North Lancing, West Sussex BN15 0PA (GB). **KNIGHT, Brian, Russell** [GB/GB]; 224 Harbour Way, Shoreham-by-Sea, West Sussex BN43 5HZ (GB).


(74) Agent: **JENNINGS, Niger, Robin;** Kilburn & Strode, 20 Red Lion Street, London WC1R 4PJ (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: **TORSIONALLY DAMPED ROTARY SHAFTS**



(57) Abstract: A rotary shaft, such as an automotive crankshaft, for rotation about an axis carries an eccentric substantially circular section, radially extending flap (6), connected to the radially outer surface of which is an annular housing (16) affording a cavity defined in part by radially inner and radially outer coaxial cylindrical surfaces. The axis (22) of the cavity is offset from the axis (4) of the shaft. The cavity accommodates an annular inertia mass (20) and the radially inner and outer surfaces of the cavity are opposed to radially inner and outer surfaces, respectively, of the inertia mass whereby there are two pairs of opposed surfaces. One of the said pairs constitutes bearing surfaces guiding relative motion of the inertia mass and the housing (16) about the axis (22) of the coaxial cylindrical surfaces. The other of the said pairs is spaced apart to define an annular space accommodating a displaceable material, such as a grease, the inertia mass and the cavity having a dimension in the radial direction which has a maximum value at a first position opposite to the direction of eccentricity and decreases progressively in both circumferential directions to a second position offset by 180° from the first position.

WO 2004/029476 A1

BEST AVAILABLE COPY

WO 2004/029476 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

BEST AVAILABLE COPY